

Medicine Transporters

Type 2.5MT Type 4 MT Type 8 MT



<p>1- Walls</p> <ul style="list-style-type: none"> • Prefabricated insulated sandwich panels assembly • Foam-in-place Polly-urethane (CFC free) • 100 mm thickness, 48 kg/m³ density • Color-coat hot dip galvanized steel white color • Polly-ethylene covered sheets to protect the panels during manufacturing process • 0.6 -mm thick external & internal cladding 	<ul style="list-style-type: none"> • Injected under high pressure & 70°c • Fire retardant • Double bend by roll-former to increase the stiffness • Tongue & groove edges to fasten the panels together with steel cam action • Locks on all panel edges • Precisely located cam lock & steel encased pin • Air tight sealed joints
<p>2- Ceiling:</p> <ul style="list-style-type: none"> • same material as wall panels 	<ul style="list-style-type: none"> • 0.6 pre-painted steel sheets for inner cladding
<p>3- Floor:</p> <ul style="list-style-type: none"> • Same material as wall panels • 12 mm treated ply-wood layer 	<ul style="list-style-type: none"> • Aluminum checkered plate covering the floor to afford heavy weights
<p>4- Doors:</p> <ul style="list-style-type: none"> • Same specs of walls • Bar locking system 	<ul style="list-style-type: none"> • Heavy-duty accessories • Heavy duty gasket to assure tightness • 270° door opening angle for each leaf
<p>5- Frame:</p> <ul style="list-style-type: none"> • 1.25 mm stainless steel angles 	<ul style="list-style-type: none"> • Cage frame • Heavy duty fastening to the truck chassis
<p>6- Lighting:</p> <ul style="list-style-type: none"> • inner low temperature lighting 	<ul style="list-style-type: none"> • Traffic signal lighting
<ul style="list-style-type: none"> • Suitable for rough roads • 1 or 2 shelves in each compartment • extra roof to provide shade for the compartment • Optional straps to tightly hold the medicine boxes 	<ul style="list-style-type: none"> • Single or multiple compartments • Each compartment is completely isolated from others • Easy loading and unloading of the truck • Tilted floor for ease of cleaning
<p>7-Sizes:</p> <ul style="list-style-type: none"> • small: 2.5 tons 3.10 X 1.70 X 1.70 mt (type 2.5MT) • Medium: 4 tons 4.35 X 2.10 X 2.00 mt (type 4MT) • Large: 8 tons 5.5 X 2.40 X 2.20 mt (type 8MT) 	
<p>8- Cooling Units:</p> <ul style="list-style-type: none"> • Operates by truck engine & electric 3 phase suitable for tropical areas. • Internal temperature adjustable from -20 to +10 optional thermograph. To provide an evidence for the temperature fluctuation versus time inside the Medicine compartment. 	

ELECTROLAB

Dallah building, 7 A Cornaish ELnil, Maadi, Zip Code 11431
 Email: email: electrolab@electrolabtrucks.com

Tel: +20-2-25285213 (4) (5) (6)

Fax: +20-2-25285212

www.electrolabtrucks.com

